

For CEE plugs and sockets  
from 16A to 32A.

**MENNEKES®**  
Plugs for the world

# Safe fixing.



#### Torsion-proof design

The torsion protection engages into the groove of the opening for installation hence locking the devices in their position.

The contact surface of the nut is provided with ribs that create a safe hold.



#### Terminals

RAPIDO panel-mounted sockets and inlets are wired prior to installation. Maximum convenience as all screws are turned in the same direction. After connection of the conductors, simply fasten the mounting ring – that's all it takes.



#### Dismantling

When new wiring is required, undo the mounting ring. Apply the screwdriver underneath the torsion protection, turn it slightly and the system is unlocked.



#### TwinCONTACT

Even faster installation. The receptacle with the new spring terminal: all it takes is insert the conductor. Also approved as a through-wiring terminal.

**Receptacles with TwinCONTACT may also be wired after installation.**



**MENNEKES®**  
Plugs for the world

MENNEKES  
Elektrotechnik GmbH & Co. KG  
Spezialfabrik für Steckvorrichtungen

P. O. Box 13 64  
D-57343 Lennestadt  
Phone +49 (0) 27 23 / 41-1  
Fax +49 (0) 27 23 / 41-2 14  
E-Mail info@MENNEKES.de  
www.MENNEKES.de

**MENNEKES®**  
Plugs for the world

# RAPIDO

## The quick turn... fixed!

The perfect connection for any application.



Save time  
with a central  
locking system.

No screws.

More information about our products can be found on the internet at [www.MENNEKES.de](http://www.MENNEKES.de)

5840005

# Swift fitting. Panel-mounted plugs and receptacles RAPIDO

The perfect technology.

Central locking with no tools.



- Save time and material – no need at all for fastening screws.
- Installation without tools.
- Screws with quick threads. Not accessible from outside, for maximum safety.
- Perfect design, also when fitted in groups.

	2p+E	3p+E	3p+N+E	Ampere	No. of poles	110V 50 and 60 Hz	230V 50 and 60 Hz	400V 50 and 60 Hz	500V 50 and 60 Hz		2p+E	3p+E	3p+N+E	Ampere	No. of poles	110V 50 and 60 Hz	230V 50 and 60 Hz	400V 50 and 60 Hz	500V 50 and 60 Hz		
<b>RAPIDO panel-mounted receptacle</b> screw-type terminals for wall openings of 61 mm, centralized fastening using swift-connect threaded lock, ⚠ IP 44				16	3	964	966				<b>RAPIDO panel-mounted inlet</b> screw-type terminals for wall openings of 61 mm, centralized fastening using swift-connect threaded lock, ⚠ IP 44				16	3	919	924			
				16	4			990						16	4			931			
				16	5			985						16	5			949			
<b>RAPIDO panel-mounted receptacle</b> screw-type terminals for wall openings of 70 mm, centralized fastening using swift-connect threaded lock, ⚠ IP 44				16	4		908	968	917		<b>RAPIDO panel-mounted inlet</b> screw-type terminals for wall openings of 70 mm, swift-connect threaded lock, ⚠ IP 44				16	4		932	933	934	
				16	5			969						16	5			972			
				32	3	918	995						32	3	935	938					
				32	4		929	999	930				32	4		939	942	944			
				32	5			976					32	5			945				
<b>RAPIDO panel-mounted receptacle with TwinCONTACT</b> spring terminals as connecting terminals, suitable for continuous wiring, for wall openings of 70 mm, centralized fastening using swift-connect threaded lock, ⚠ IP 44				16	5			907			<b>RAPIDO phase inverter</b> as panel-mounted inlet, screw-type terminals for wall openings of 70 mm, centralized fastening using swift-connect threaded lock, ⚠ IP 44				16	5			937		

■ More information about our products can be found on the internet at [www.MENNEKES.de](http://www.MENNEKES.de)

■ **Please note:** for RAPIDO inlets, a latching nose must be provided by the customer to accommodate the coupling cover.